



- ① NOROC-L INSULATED WALL PANEL  
MINERAL FIBER
- ② "SILKLINE" TYPE EXTERIOR PROFILE
- ③ PREPAINTED BASE TRIM  
FOR HIDDEN FIXATION ANGLE CAPPING
- ④ CONCRETE FOUNDATION (BY OTHERS)
- ⑤ VAPOR BARRIER MEMBRANE (SELF ADHESIVE)
- ⑥ BACKER ROD FOAM WITH  
SEALANT AND WEEP HOLE  
AT EACH PANEL JOINT
- ⑦ POLYETHYLENE STRIP  
1/2" x 2" - DENSITY: 2 lb / FT<sup>3</sup>  
P/N: 0307-00015
- ⑧ 5" NOREX WALL FASTENER  
14 Ga. GALV. STEEL  
P/N: 0310-00036
- ⑨ FACTORY APPLIED BUTYL SEALANT
- ⑩ 2 x SCREW  
SEE THE SCREW AND GIRT  
SELECTION GUIDE, NA-IC 10,10
- ⑪ STRUCTURAL GIRT (BY OTHERS)  
SEE THE SCREW AND GIRT  
SELECTION GUIDE, NA-IC 10,10
- ⑫ STRUCTURAL ANGLE " L" 3" x 3" x 3/16"  
(BY OTHER)
- ⑬ DECOMPRESSION CHAMBER
- ⑭ SEALANT OR CONTINUOUS BUTYL