

ENVIRONMENTAL DATA SHEET

NOROC®



PRODUCT CONTRIBUTION SUMMARY

LEED® v4 requirements for Building Design + Construction (BD+C)

New Construction, Core and Shell, Schools, Retail, Data Centers, Warehouse and Distribution Centers, Hospitality and Healthcare.

LEED® v4 requirements for Interior Design + Construction (ID+C)

Commercial Interiors, Retail and Hospitality.

MATERIALS AND RESOURCES		PRODUCT CONTRIBUTIONS	
MR	Building Product Disclosure and Optimization – Environmental Product Declaration (EPD) Option 1: Environmental Product Declaration (1 point) The product contributes to this credit due to the availability of a product specific EPD (Type III) and is valued as 1 whole product out of the 20 needed for the purposes of credit achievement.	Contribute	ENVIRONMENTAL IMPACTS Product-specific EPD Type III EPD compliant to ISO 14025:2006
MR	Building Product Disclosure and Optimization – Sourcing of Raw Materials Option 2: Leadership extraction practices (1 point) Product meets at least one of the responsible extraction criteria: recycled content, wood product certification, biobased materials, extended producer responsibility.	Contribute	ATTRIBUTES Recycled content Pre-consumer: 34.8% Post-consumer: 16.9%
MR	Building Product Disclosure and Optimization – Material Ingredients Option 1: Material ingredients reporting (1 point) The product contributes to this credit due to the availability of Health Product Declarations®. They are valued as 1 whole product out of the 20 needed for the purposes of credit achievement.	Contribute	INGREDIENTS AND EMISSIONS HPD® version 2.2 Health Product Declaration®
INDOOR ENVIRONMENTAL QUALITY		PRODUCT CONTRIBUTIONS	
EQ	Low-Emitting Materials Option 1: Product category calculation (1-3 points) The number of points depends on the LEED® rating system chosen and the number of compliant categories. For the Ceilings, Walls, Thermal, and Acoustic Insulation category, 100 % of ceilings, walls, thermal, and acoustic insulation must meet the general emissions evaluation. Additional conditions apply for healthcare and schools. Batt insulation products may contain no added formaldehyde, including urea formaldehyde, phenol formaldehyde, and urea-extended phenol formaldehyde.	Does not contribute	INGREDIENTS AND EMISSIONS The product was not tested and determined compliant in accordance with California Department of Public Health (CDPH) Standard Method (CDPH) v1.2-2017. (The Noroc® architectural panel does not contain any added formaldehyde, including urea formaldehyde, phenol formaldehyde, and urea-extended phenol formaldehyde.)

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and its integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, caused in all or in part, by errors and omissions relative to the collection, compilation and/or interpretation of data.

Validated Eco-Declaration:

VED17-1061-03

Period of validity:

2022/09 to 2023/09

©Copyright 2016 Vertima inc.



ENVIRONMENTAL DATA SHEET

NOROC®



PRODUCT CONTRIBUTION SUMMARY

LEED® v4 requirements for Building Design + Construction (BD+C)

New Construction, Core and Shell, Schools, Retail, Data Centers, Warehouse and Distribution Centers, Hospitality and Healthcare.

LEED® v4 requirements for Interior Design + Construction (ID+C)

Commercial Interiors, Retail and Hospitality.

ENERGY AND ATMOSPHERE		PRODUCT CONTRIBUTIONS	
EA Prerequisite 2	Minimum Energy Performance Option 1: Whole-building energy simulation or at the scale of the rental space, according to the system Option 2: Prescriptive compliance: ASHRAE 50% Advanced Energy Design Guide Option 3: Prescriptive compliance: Advanced Buildings™ Core Performance™ Guide	Contribute	TECHNICAL PERFORMANCES The Noroc® architectural panel contributes to this prerequisite. Its polyurethane insulation has a thermal insulation factor of R-4 per inch of thickness.
EA	Optimize Energy Performance Option 1: Whole-building energy simulation or at the scale of the rental space, according to the system BD+C (1-20 points) and ID+C (1-25 points) Option 2: Prescriptive compliance: ASHRAE Advanced Energy Design Guide BD+C (1-6 points) and ID+C (1-16 points)	Contribute	TECHNICAL PERFORMANCES The Noroc® architectural panel contributes to this prerequisite. Its polyurethane insulation has a thermal insulation factor of R-4 per inch of thickness.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and its integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, caused in all or in part, by errors and omissions relative to the collection, compilation and/or interpretation of data.

Validated Eco-Declaration:

VED17-1061-03

Period of validity:

2022/09 to 2023/09

©Copyright 2016 Vertima inc.

