

Project #: Non Specific

Boucherville, QC, March 30 2022

## CONTEXT

- Advantica-L Control is a PVC laminated steel manufactured by Tata Steel. This product superior protection from corrosion, stains, marks, and food emissions, and is anti-static, reducing retention of dust and dirt, meaning easier maintenance and longer durability. Advantica-L is characterized by its smooth, slightly textured finish, and offers superior resistance to humidity and chemicals. The flexibility and robustness of this laminated steel results in it being dirt resistant and food safe, making it the ideal product to minimize the risk of surface contamination.
- Even if this material is highly resistant, it is possible to scratch and damage this material. It is possible to repair small damages following the procedure below.



## REPAIR PROCEDURE

1. Make sure the scratch is free from lifting material on the scratch edges by rubbing the edges with your fingernail
2. Clean surface with Isopropyl Alcohol 70% and wait for the alcohol to evaporate completely before going to next step
3. Use Genicolor touch up paint for doors and windows - Ice White #429 - Article #429 to proceed with touch up, following the instructions provided with the touch up pen
4. Let dry for 20-30 minutes before exposing to dust.
5. The paint will be completely cured (hardened) after 24 hours.
6. If required, apply a second coat on the scratch
  - There are no other caustic products involved in the cleaning of the wall partitions and that the operating temperature is well below 30 C, The Advantica-L will perform well.



For questions and comments, please contact our technical sales representative,

**Alexandre Belisle**  
Director R-D and Technical services